



## PLYWOOD DECKING

### MANUFACTURER'S PRODUCT INFORMATION SHEET

#### DESCRIPTION

Plywood Decking is a specialty plywood panel engineered and manufactured to meet the performance criteria of the marine industry. Carefully manufactured for strength and flatness, it is a high quality, economical alternative to traditional plywood grades where one of two fully repaired faces are required.

#### CONSTRUCTION

Plywood Decking is manufactured from selected veneers and marine glue. Balanced construction techniques are used to maintain strength and flatness. Plywood Decking is made with high grade "C" inner plies and restricted core gaps for overall panel integrity.

#### SPECIFICATIONS

Species: All fir and larch

Moisture Content: Target mc of panels: 10%-12%

Glue Bond: Marine-type high solid content exterior glue.

Face Defect: Tight-knot solid face allowing no open defects.

Fully sanded for receiving carpet or other resilient floor coverings. repaired - no knotholes.  
Core: Tightly laid selected high grade "C" veneer.  
Back: High grade "C" veneer with a 60 grit touch sand selected to minimize knotholes or splits.

Minimum number of Plies:

1/4" & 3/8" : 3-ply

5/8" : 5-ply or 7-ply

1" : 7-ply or 9-ply

1/2" : 4-ply or 5-ply

3/4" : 5-ply or 7-ply

1-1/2" : 11-ply or 13-ply

Sizes: Standard thickness 1/4" through 3" in 4' x 8' through 8' x 50' sheets

Standard Packaging for 4'x 8': Three straps with stickers and corner protectors.

Shipping Weight:

1/4": 22 lbs. per sheet

5/8": 52 lbs. per sheet

1": 80 lbs. per sheet

3/8": 29 lbs. per sheet

3/4": 62 lbs. per sheet

1-1/2": 125 lbs. per sheet

1/2": 40 lbs. per sheet

#### USES

Plywood Decking is used wherever panels are needed, such as floors, decking and bulkheads in boats or any place a good faced, structural panel is required. Panels are manufactured to offer an excellent wear surface for passenger or cargo caused uniform or dynamic loads. Flooring materials can be effectively and easily laminated to Plywood Decking. GW Industries also offers preservative treated plywood for various applications, ask for XP panels.

#### WARRANTY

Plywood Decking is guaranteed against delamination and manufacturing defects for the life of the panel.

GW Industries will not be held responsible for damage caused by improper installation, or assume any liability for consequential damages.

GW Industries, Inc.

Corporate Address: 9450 SW Commerce Circle # 101 \* Wilsonville Oregon 97070

Phone (503) 682-9095 \* Toll Free: (866) 504-9095 \* Fax: (503) 682-9098

www.gwi.us.com \* email: info@gwi.us.com